



SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 6/5/2024 Revision date: 6/5/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SPEED
Product code : 425

1.2. Recommended use and restrictions on use

Recommended use : Automotive Care Products, Polishing agent
Restrictions on use : None known

1.3. Supplier

3D International
20724 Centre Pointe Pkwy #1
Santa Clarita, CA 91350
T 888-999-7627

1.4. Emergency telephone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)
CHEMTREC 1-800-424-9300 (in the US & Canada)
1-703-527-3887 (Outside the US)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	15-40

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Name	Product identifier	%
Aluminum Oxide	CAS-No.: 1344-28-1	10-30
Glycerin	CAS-No.: 56-81-5	1 – 5
Propan-2-ol, isopropyl alcohol, isopropanol	CAS-No.: 67-63-0	1 – 5
White Mineral Oil (Petroleum)	CAS-No.: 8042-47-5	1 – 5

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : No first aid should be needed.
First-aid measures after skin contact : Wash with soap and water. Seek medical attention if irritation develops.
First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion : Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin : Prolonged or repeated contact may cause skin to become dry. May cause slight irritation to the skin.
Eyes : May cause minor eye irritation.
Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms : None known.

4.3. Immediate medical attention and special treatment, if necessary

Not required.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : None.

5.2. Specific hazards arising from the chemical

Fire hazard : This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.

6.1.1. For non-emergency personnel

Emergency procedures : Keep unnecessary and unprotected personnel away from the spillage.

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.
Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Ensure adequate ventilation.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : No special storage required.
Incompatible materials : None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

White Mineral Oil (Petroleum) (8042-47-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Aluminum Oxide (1344-28-1)	
USA - OSHA - Occupational Exposure Limits	
Local name	alpha-Alumina

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Aluminum Oxide (1344-28-1)	
OSHA PEL (TWA)	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Glycerin (56-81-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL (TWA)	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL (TWA)	980 mg/m ³ 400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : No particular/specific measures required.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
In case of repeated or prolonged contact wear gloves. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Use suitable eye protection

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not required for normal conditions of use. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Cream.
Color	: Purple
Odor	: Fruity
Odor threshold	: No data available
pH	: 7 – 9
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.03
Solubility	: Partially soluble. water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 3000 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.

9.2. Other information

VOC content : < 1 % Tested using liquid component

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

White Mineral Oil (Petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h No mortality

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 6.8 mg/l/4h

Aluminum Oxide (1344-28-1)

LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 7.6 mg/l 1 h

Glycerin (56-81-5)

LD50 oral rat	27200 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral)
LD50 oral	25000 mg/kg body weight
LD50 dermal	56750 mg/kg (4 day(s), Guinea pig, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.75 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Converted value, Inhalation (vapours))
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapours)	> 2.75 mg/l Source: ECHA

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 Inhalation - Rat [ppm]	1666.66 ppm/1h
ATE US (oral)	5840 mg/kg body weight
ATE US (dermal)	16400 mg/kg body weight

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
ATE US (gases)	833.33 ppmV/4h
Skin corrosion/irritation	: Not classified pH: 7 – 9
Serious eye damage/irritation	: Not classified pH: 7 – 9
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Distallates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male
Aluminum Oxide (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
White Mineral Oil (Petroleum) (8042-47-5)	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg body weight
Aluminum Oxide (1344-28-1)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: Not classified
Viscosity, kinematic	: > 3000 mm ² /s @40°C
White Mineral Oil (Petroleum) (8042-47-5)	
Viscosity, kinematic	> 3 mm ² /s
Hydrocarbon	Yes
Distallates (petroleum), hydrotreated light (64742-47-8)	
Viscosity, kinematic	1.764 mm ² /s @40C
Glycerin (56-81-5)	
Viscosity, kinematic	1119.746 mm ² /s
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Viscosity, kinematic	2.58 mm ² /s
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: Prolonged or repeated contact may cause skin to become dry. May cause slight irritation to the skin.
Eyes	: May cause minor eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Chronic symptoms : None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

White Mineral Oil (Petroleum) (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 100 mg/l
Distallates (petroleum), hydrotreated light (64742-47-8)	
EC50 - Crustacea [1]	> 1000 mg/l
Aluminum Oxide (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Glycerin (56-81-5)	
LC50 - Fish [1]	54000 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 10000 mg/l
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Pimephales promelas (Fathead minnow)
EC50 - Crustacea [1]	> 10000 mg/l
LC50 - Fish [2]	9640 mg/l Pimephales promelas (Fathead minnow)
NOEC chronic crustacea	3.37 mg/l

12.2. Persistence and degradability

SPEED	
Persistence and degradability	No additional information available.
White Mineral Oil (Petroleum) (8042-47-5)	
Persistence and degradability	Rapidly degradable
Distallates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Rapidly degradable
Biodegradation	85 % OECD 301F (28d)
Aluminum Oxide (1344-28-1)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds..

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Glycerin (56-81-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
ThOD	1.217 g O ₂ /g substance
BOD (% of ThOD)	0.71
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Glycerin (56-81-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.75 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Not bioaccumulative.
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
BCF - Fish [1]	3
Partition coefficient n-octanol/water (Log Kow)	0.05

12.4. Mobility in soil

Glycerin (56-81-5)	
Surface tension	0.0634 N/m (20 °C, 1000 g/l)
Ecology - soil	No (test)data on mobility of the substance available.
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

DOT	TDG	IMDG	IATA
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

SPEED

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum Oxide	CAS-No. 1344-28-1	10-30%
Nonylphenol, ethoxylated	CAS-No. 9016-45-9	≥ 0.2625%

15.2. International regulations

CANADA

White Mineral Oil (Petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

SPEED

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum Oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

Glycerin (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations


No additional information available

National regulations

SPEED

Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

 **WARNING:** This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Aluminum Oxide(1344-28-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
Glycerin(56-81-5)	U.S. - New Jersey - Right to Know Hazardous Substance List
Propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 6/5/2024

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.