



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

SECTION 1: Identification

1.1 Product identifier

Trade name **Adam's Paint Correcting Polish**
ADP497-01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polishing compound
Professional use
Industrial use

HS code 3405.30.00.

1.3 Details of the supplier of the safety data sheet

Adam's Polishes Inc.
8225 North Valley Hwy.
Thornton CO 80221
720-484-5059

tips@adamspolishes.com
www.adamspolishes.com

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	Skin Irrit. 2	H315
A.4S	skin sensitization	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

none

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	alpha-alumina	1344-28-1	PEL		15					dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	ACGIH® 2019
US	glycerine	56-81-5	PEL		15					mist, dust	29 CFR 1910.1000
US	glycerine	56-81-5	PEL		5					mist, r	29 CFR 1910.1



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0

Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
											000
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	mineral oil	8042-47-5	TLV®		5					i, ex-Met-Work-Fl	AC-GIH® 2019

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur as dust

exMetWorkFl excluding metal working fluids

i inhalable fraction

mist as mists

r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
White mineral oil (petroleum)	8042-47-5	DNEL	165 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
White mineral oil (petroleum)	8042-47-5	DNEL	217 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Orange oil, sweet	8008-57-9	DNEL	31 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Orange oil, sweet	8008-57-9	DNEL	8.9 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Orange oil, sweet	8008-57-9	DNEL	186 µg/cm ²	human, dermal	worker (industry)	acute - local effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Orange oil, sweet	8008-57-9	PNEC	44 mg/kg	aquatic organisms	water	short-term (single instance)
Orange oil, sweet	8008-57-9	PNEC	5.8 µg/l	aquatic organisms	water	intermittent release
Orange oil, sweet	8008-57-9	PNEC	5.4 µg/l	aquatic organisms	freshwater	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Orange oil, sweet	8008-57-9	PNEC	0.54 µg/l	aquatic organisms	marine water	short-term (single instance)
Orange oil, sweet	8008-57-9	PNEC	2.1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Orange oil, sweet	8008-57-9	PNEC	1.3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Orange oil, sweet	8008-57-9	PNEC	0.13 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Orange oil, sweet	8008-57-9	PNEC	0.26 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	light orange
Particle	not relevant (liquid)
Odor	fruity



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Other safety parameters

pH (value)	8 – 8.5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101 kPa >212 °C at 1 atm
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	19 vol%
Vapor pressure	32 hPa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>220 °C (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	10,000 mm ² /s at 25 °C
- Dynamic viscosity	10,500 cP at 25 °C
Explosive properties	none
Oxidizing properties	none

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215 °C)
--	--

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
White mineral oil (petroleum)	8042-47-5	dermal	>2,000 mg/kg
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	>5 mg/l/4h

Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
C9-C15 mixed cycloalkanes and alkanes	64742-47-8	oral	LD50	>5,000 mg/kg	rat
C9-C15 mixed cycloalkanes and alkanes	64742-47-8	dermal	LD50	>2,000 mg/kg	rabbit
distillates (petroleum) hydrotreated, light	64742-47-8	oral	LD50	>5,000 mg/kg	rat
distillates (petroleum) hydrotreated, light	64742-47-8	inhalation: vapor	LC50	>5,000 mg/l/4h	rat
distillates (petroleum) hydrotreated, light	64742-47-8	dermal	LD50	>5,000 mg/kg	rabbit
White mineral oil (petroleum)	8042-47-5	oral	LD50	>5,000 mg/kg	rat
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	LC50	>5 mg/l/4h	rat
White mineral oil (petroleum)	8042-47-5	dermal	LD50	>2,000 mg/kg	rabbit
Naphtha (petroleum), hydrotreated heavy	64742-48-9	oral	LD50	>5,000 mg/kg	rat
Naphtha (petroleum), hydrotreated	64742-48-9	dermal	LD50	>2,000 mg/kg	rabbit



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
heavy					
Orange oil, sweet	8008-57-9	oral	LD50	>5,000 mg/kg	rat
Orange oil, sweet	8008-57-9	dermal	LD50	>5,000 mg/kg	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
White mineral oil (petroleum)	8042-47-5	LL50	>10,000 mg/l	fish	96 h
Orange oil, sweet	8008-57-9	LL50	5.7 mg/l	fish	96 h
Orange oil, sweet	8008-57-9	EL50	1.4 mg/l	aquatic invertebrates	24 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EC50	15 mg/l	microorganisms	40 h



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|---|---|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not relevant |
| 14.3 Transport hazard class(es) | none |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

Cleaning Product Right to Know Act Substance List (CA-RTK)			
Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
aluminium oxide	1344-28-1	abrasive	
C9-C15 mixed cycloalkanes and alkanes	64742-47-8	solvents	
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
Glycerine	56-81-5	humectant	
White mineral oil (petroleum)	8042-47-5	lubricant	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B
Alcohols, C11-15- secondary, ethoxylated	84133-50-6	surfactant	
acrylate copolymer	75760-37-1	viscosity modifier	
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	surfactant	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	solvents	EC Annex VI CMRs - Cat. 1B
benzyl benzoate	120-51-4	fragrance	EU Fragrance Allergens
Orange oil, sweet	8008-57-9	fragrance	
grapefruit oil terpenes	68917-32-8	fragrance	
2,2'-iminodiethanol	111-42-2	impurity	CA TACs IARC Carcinogens - 2B OEHHA RELs Prop 65
cyclamen aldehyde	103-95-7	fragrance	
benzyl salicylate	118-58-1	fragrance	
2-methylpentane-2,4-diol	107-41-5	humectant	
2-(4-tert-butylbenzyl)propionaldehyde	80-54-6	fragrance	EU Fragrance Allergens



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
benzyl alcohol	100-51-6	fragrance	
Allyl hexanoate	123-68-2	fragrance	
allyl cyclohexylpropionate	2705-87-5	fragrance	
ethyl vanillin	121-32-4	fragrance	
ethyl maltol	4940-11-8	fragrance	
7-hydroxycitronellal	107-75-5	fragrance	EU Fragrance Allergens
Phenethyl alcohol	60-12-8	fragrance	

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
diethanolamine	111-42-2	0.025		cancer
1,4-dioxane	123-91-1	0.000003		cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 14 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 14 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water,



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0
Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Category	Rating	Description
		polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazards
Health: health hazard
Personal protection: personal protective equipment (PPE) for normal use
Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

Additional information

The contained substances are listed in the following national inventories:
DSL/NDSL (Canada)
TSCA (United States)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
Restructuring: section 9, section 14



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0

Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	Trade name: Adam's Paint Correcting Polish	Trade name: Adam's Paint Correcting PolishADP497-01	yes
3.2		Hazardous ingredients acc. to GHS: change in the listing (table)	yes
3.2	Remarks: For full text of abbreviations: see SECTION 16.	Remarks: For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
9.1	Density: 1.1 – 1.1 g/ml	Density: not determined	yes
9.1		Relative density: Information on this property is not available	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
11.1		Acute toxicity of components: change in the listing (table)	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1		Additional information: The contained substances are listed in the following national inventories: DSL/NDSL (Canada) TSCA (United States)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0

Replaces version of: 2024-04-03 (GHS 10)

Revision: 2024-11-22

Abbr.	Descriptions of used abbreviations
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Adam's Paint Correcting Polish

Version number: GHS 11.0

Revision: 2024-11-22

Replaces version of: 2024-04-03 (GHS 10)

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.