

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

SECTION 1: Identification

1.1 Product identifier

Trade name

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Alternative name(s)

Everyday Diesel Treatment® (EDT®) 2025, Everyday Diesel Treatment (EDT) with LX4®, EDT w/LX4, Doc's Diesel The Diesel Treatment

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

general use

1.3 Details of the supplier of the safety data sheet

Lubrication Specialties, LLC
3975 Morrow Meadows Drive
Mount Gilead Ohio 43338
United States

Telephone: +1 800-341-6516
e-mail: lab@lubricationspecialties.com
Website: <https://www.hotshotssecret.com/>

e-mail (competent person)

richard@lubricationspecialties.com (Richard Benson)

1.4 Emergency telephone number

Emergency information service

This number is only available during the following office hours: Mon-Fri 08:00 AM - 04:30 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.10	acute toxicity (oral)	4	Acute Tox. 4	H302
A.1D	acute toxicity (dermal)	4	Acute Tox. 4	H312
A.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
A.6	carcinogenicity	2	Carc. 2	H351
A.7	reproductive toxicity	2	Repr. 2	H361
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

- Pictograms

GHS07, GHS08



- Hazard statements

H227 Combustible liquid.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201 Obtain special instructions before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P302+P352 If on skin: Wash with plenty of water.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 Call a poison center/doctor if you feel unwell.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Naphthalene, 2-Ethylhexyl nitrate, 1H-Benzotriazole -4 or 5-methyl, Xylene

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Risk of explosion if heated under confinement.
Repeated exposure may cause skin dryness or cracking.
Contains 2,4,6-tri-tert-butylphenol. May produce an allergic reaction.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
2-Ethylhexyl nitrate	CAS No 27247-96-7	50 – < 75	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Flam. Liq. 4 / H227	
Solvent naphtha, petroleum, heavy aromatic	CAS No 64742-94-5	5 – < 10	Flam. Liq. 3 / H226	
Trade Secret	CAS No Trade Secret	5 – < 10	Flam. Liq. 4 / H227	
2-ethylhexan-1-ol	CAS No 104-76-7	1 – < 5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Flam. Liq. 4 / H227	
phenol, 2,6-di-tert-butyl-	CAS No 128-39-2	1 – < 5	Skin Irrit. 2 / H315	
Xylene	CAS No 1330-20-7	1 – < 5	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
2,4,6-tri-tert-butylphenol	CAS No 732-26-3	< 1	Acute Tox. 3 / H301 Skin Sens. 1B / H317 STOT RE 1 / H372	
Naphthalene	CAS No 91-20-3	< 1	Acute Tox. 4 / H302 Carc. 2 / H351	
Ethylbenzene	CAS No 100-41-4	< 1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
1H-Benzotriazole -4 or 5-methyl	CAS No 29385-43-1	< 1	Acute Tox. 4 / H302 Repr. 2 / H361	

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							ACGIH® 2025
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	2-ethyl-1-hexanol	104-76-7	TLV®	5							ACGIH® 2025

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	xylene, mixture of isomers	1330-20-7	TLV®	20							ACGIH® 2025
US	xylene (dimethylbenzene)	1330-20-7	PEL (CA)	100	435	150	655	300			Cal/OSHA PEL
US	xylenes (o-, m-, p-isomers)	1330-20-7	PEL	100	435						29 CFR 1910.1000
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1000
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5					H	Cal/OSHA PEL
US	naphthalene	91-20-3	TLV®	10	52					H	ACGIH® 2025

Notation

- Ceiling-C ceiling value is a limit value above which exposure should not occur
H absorbed through the skin
STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	sum of mandelic acid and phenylglyoxylic acid	crea, crea-limit3c	BEI®	0.15 g/g	ACGIH® 2025
US	xylene	methylhippuric acids	crea, crea-limit3c	BEI®	0.3 g/g	ACGIH® 2025

Notation

- crea creatinine
crea-limit3c acceptable limits on urine specimens: creatinine concentration: >0.3 g/L and <3.0 g/L, specific gravity: >1.010 and <1.030

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-Ethylhexyl nitrate	27247-96-7	DNEL	0.35 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-Ethylhexyl nitrate	27247-96-7	DNEL	1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-Ethylhexyl nitrate	27247-96-7	DNEL	44 µg/cm ²	human, dermal	worker (industry)	chronic - local effects
Trade Secret	Trade Secret	DNEL	308 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Trade Secret	Trade Secret	DNEL	283 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-ethylhexan-1-ol	104-76-7	DNEL	12.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-ethylhexan-1-ol	104-76-7	DNEL	23 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
phenol, 2,6-di-tert-butyl-	128-39-2	DNEL	70.61 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
phenol, 2,6-di-tert-butyl-	128-39-2	DNEL	11.25 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2,4,6-tri-tert-butyl-phenol	732-26-3	DNEL	0.1 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2,4,6-tri-tert-butyl-phenol	732-26-3	DNEL	0.3 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
2,4,6-tri-tert-butyl-phenol	732-26-3	DNEL	0.06 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2,4,6-tri-tert-butyl-phenol	732-26-3	DNEL	1.8 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
Ethylbenzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Ethylbenzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Ethylbenzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.8 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.08 µg/l	aquatic organisms	marine water	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.74 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.74 µg/kg	aquatic organisms	marine sediment	short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-Ethylhexyl nitrate	27247-96-7	PNEC	0.191 µg/kg	terrestrial organisms	soil	short-term (single instance)
Trade Secret	Trade Secret	PNEC	19 mg/l	aquatic organisms	freshwater	short-term (single instance)
Trade Secret	Trade Secret	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Trade Secret	Trade Secret	PNEC	4,168 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Trade Secret	Trade Secret	PNEC	70.2 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Trade Secret	Trade Secret	PNEC	7.02 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Trade Secret	Trade Secret	PNEC	2.74 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.017 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.002 mg/l	aquatic organisms	marine water	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.284 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.028 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.047 mg/kg	terrestrial organisms	soil	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	0.001 mg/l	aquatic organisms	freshwater	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	0.317 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	0.032 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
phenol, 2,6-di-tert-butyl-	128-39-2	PNEC	0.697 mg/kg	terrestrial organisms	soil	short-term (single instance)
Xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
Xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
Xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organ-	soil	short-term (single

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
				isms		instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	0 mg/l	aquatic organisms	freshwater	short-term (single instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	1.368 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	0.137 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2,4,6-tri-tert-butylphenol	732-26-3	PNEC	0.274 mg/kg	terrestrial organisms	soil	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Ethylbenzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	amber
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	139.1 °C at 1,013 hPa
Flash point	>65 °C at 1,013 hPa
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	14 vol%
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	0.924 at 60 °F (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	207 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Liquid content	94.5 %
----------------	--------

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Solid content	1.278 %
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Danger of explosion, Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

- Acute toxicity estimate (ATE)

Oral	>890 mg/kg
Dermal	>1,658 mg/kg
Inhalation: gas	5,000 ppmV/4h
Inhalation: vapor	>18.61 mg/l/4h

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
2-Ethylhexyl nitrate	27247-96-7	oral	500 mg/kg
2-Ethylhexyl nitrate	27247-96-7	dermal	1,100 mg/kg
2-Ethylhexyl nitrate	27247-96-7	inhalation: vapor	11 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	dermal	>2,000 mg/kg

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
2-ethylhexan-1-ol	104-76-7	inhalation: vapor	>11 mg/l/4h
Xylene	1330-20-7	dermal	1,100 mg/kg
Xylene	1330-20-7	inhalation: vapor	11 mg/l/4h
2,4,6-tri-tert-butylphenol	732-26-3	oral	>200 mg/kg
Naphthalene	91-20-3	oral	500 mg/kg
Ethylbenzene	100-41-4	inhalation: vapor	11 mg/l/4h
1H-Benzotriazole -4 or 5-methyl	29385-43-1	oral	720 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains 2,4,6-tri-tert-butylphenol. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Xylene	1330-20-7	3	
Ethylbenzene	100-41-4	2B	
Naphthalene	91-20-3	2B	

Legend

- 2B Possibly carcinogenic to humans
3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States): Report on Carcinogens			
Name of substance	CAS No	Classification	Number
Naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens

Reproductive toxicity

Suspected of damaging the unborn child. Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

DOT	Environmentally hazardous substance, liquid, n.o.s.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.

14.3 Transport hazard class(es)

DOT	9
-----	---

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

IMDG-Code	9
ICAO-TI	9
14.4 Packing group	
DOT	III
IMDG-Code	III
ICAO-TI	III
14.5 Environmental hazards	hazardous to the aquatic environment
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., 9, III
Reportable quantity (RQ)	9,847 lbs (4,471 kg) (Naphthalene) (Xylene)
Danger label(s)	9, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	8, 146, 173, 335, 441, IB3, T4, TP1, TP29
ERG No	171

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	yes (hazardous to the aquatic environment) (2-Ethylhexyl nitrate)
Danger label(s)	9, fish and tree



Special provisions (SP)	274, 335, 375, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	9, fish and tree



Special provisions (SP)	A97, A158, A197, A215
-------------------------	-----------------------

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Excerpted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
Xylene	1330-20-7		1986-12-31
Ethylbenzene	100-41-4		1986-12-31
Naphthalene	91-20-3		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
Xylene	1330-20-7		1 3 4	100 (45,4)
Ethylbenzene	100-41-4		1 2 3	1000 (454)
Naphthalene	91-20-3		1 2 3 4	100 (45,4)

Legend

- "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- "2" indicates that the source is section 307(a) of the Clean Water Act
- "3" indicates that the source is section 112 of the Clean Air Act
- "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs IRIS Neurotoxicants OEHA RELs

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Name of substance	CAS No	Functionality	Authoritative Lists
2,4,6-tri-tert-butylphenol	732-26-3		Canada PBITs EC Annex VI CMRs - Cat. 1B EC PBTs OSPAR Priority Action Part A
Naphthalene	91-20-3		ATSDR Neurotoxicants CA NLS CA TACs CWA 303(c) CWA 303(d) IARC Carcinogens - 2B IRIS Neurotoxicants NTP 13th RoC - reasonable OEHHA RELs Prop 65 U.S. EPA NWMP PBTs
Ethylbenzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Xylene	1330-20-7				1.0 %
Ethylbenzene	100-41-4				0.1 %
Naphthalene	91-20-3				0.1 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Trade Secret	34590-94-8	A, O	
Xylene	1330-20-7	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Trade Secret	34590-94-8		F2
Xylene	1330-20-7		F3
Ethylbenzene	100-41-4		CA F3
Naphthalene	91-20-3		CA F2

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Legend

CA Carcinogenic
F2 Flammable - Second Degree
F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANOL, (2-METHOXYMETHYLETHOXY)-	34590-94-8	
BENZENE, DIMETHYL-	1330-20-7	E
BENZENE, ETHYL-	100-41-4	E
NAPHTHALENE	91-20-3	E
1-HEXANOL, 2-ETHYL-	104-76-7	

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Trade Secret	34590-94-8	T
Xylene	1330-20-7	T, F
Xylene	1330-20-7	T, F
Xylene	1330-20-7	T, F
Ethylbenzene	100-41-4	T, F
Naphthalene	91-20-3	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
naphthalene	91-20-3		cancer

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	1	irritation or minor reversible injury possible
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Category	Rating	Description
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed or exempt from listing
CA	NDSL	all ingredients are listed
CA	DSL	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
NDSL Non-domestic Substances List (NDSL)
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2025	From ACGIH®, 2025 TLVs® and BEIs® Book. Copyright 2025. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
ED	Endocrine disruptor
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Hot Shot's Secret® Everyday Diesel Treatment® (EDT®)

Version number: GHS 3.0
Replaces version of: (GHS 2. 2)

Revision: 2026-01-13

Abbr.	Descriptions of used abbreviations
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.